

MTBE

USE: HIGH OCTANE COMPONENT FOR GASOLINE

PROPERTY	MU	LIMITS		TEST METHOD
		Min.	Max.	
Purity	%(m/m)	97	-	Chromatographic
Water	mg/kg	-	500	SR EN ISO 12937:01 ¹
Density at 20°C	Kg/m ³	735	750	ASTM D 4052-96 (02) ¹ / ASTM D 1298-99 ¹ (05) / SR EN ISO 3675:02 ¹ / SR EN ISO 12185:02 ¹

NOTA: 1) Accredited test by RENAR

Quality control: control is done on lot.

Each batch will have max.1300 tone for delivery in tank wagons or tank capacity for pipelines. The lot will have product of same type.

During testing,the product must comply with all parameters depicted in standard specification for corresponding product/type.If not,the batch is rejected.

In case of litigious, the quality control will be done using the samples kept for these cases, sampling being done in accordance with the sampling procedure.

NOTE: A sample is analyzed in the supplier laboratory, and the second is kept for three months after delivery, at buyer's disposal, for an eventual control.

Sampling procedure: according to SR EN ISO 3170:2004 / SR EN ISO 3170:2004/C91:05/ASTM D 4057- 06

Informations about handling, transportation and storage: according to "Material Safety Data Sheet" FDS-2.8 T.

Quality-environment-safety integrated Management System is certified by Germanischer Lloyd Certification according to the following standards:

- ISO 9001:2008
- ISO 14001:2004
- BS OHSAS 18001:2007

The test lab is accredited by RENAR, in compliance with SR EN ISO/CEI 17025:2005.

© **ROMPETROL REFINING SA** Unauthorised reproduction by any mean, partial or total, is prohibited.